



Clear Choice®
TRANSPARENT APPLICATION TAPE

AT60n



PRODUCT DESCRIPTION

AT60n features a one side embossed polypropylene backing with excellent clarity, abrasion resistance and lay flat characteristics. Its acrylic adhesive is designed for clean pick up and transfer performance on all brands of cast or calendared vinyl. The stable and plasticizer-resistant adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage, therefore transfer is never a problem.

Adhesive	Modified polyacrylate
Color	Clear embossed, polypropylene
Caliper, facestock	3.7 mils (94µm)
Caliper, facestock + adhesive	4.1 mils (104µm)
Adhesion to Stainless Steel	1 – 3 oz./inch width (1 N/25mm)
Tensile	3600 psi (25 MPa)
Elongation	700%
Tear Resistance (grams)	n/a
Shelf life Stored at 22°C (72°F)/ 50-55 % RH	1 year

FEATURES & BENEFITS

RTape's AT60n Application Film combines many of the features of our most popular film products:

- Excellent lay flat to resist curling.
- Lower static for easier handling.
- Better adhesion across a wider range of vinyl films.
- Forgiving adhesive system! If the adhesive side of the film accidentally folds onto itself, AT60n pulls apart easily without adhesive delamination!
- Outstanding clarity to aid precise registration of multi-color overlays.
- Rigid polypropylene facestock minimizes misalignment problems.
- Easier unwind eliminates exhausting application tape struggles.
- Unique adhesive system will not build to vinyl during storage of graphics. Trouble-free release from graphics following vinyl application.

APPLICATIONS

- General purpose application tape for wet and dry applications.

Important Notice: All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because RTape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

RTape Corp.

6 Ingersoll Road, South Plainfield, NJ 07080
908-753-5570 Fax 908-753-5014 800-440-1250
E-mail: sales@rtape.com
www.rtape.com

Represented in Europe by

Industrial Consultants

Industriezone Langevoorde
Groendreef 35
9880 Aalter, Belgium
Ph: (+) 32.9.216.6700
FAX: (+) 32.9.216.6709
sales@rtape.eu

RESPONSIVE. RELIABLE. RESOURCEFUL.