



Tape Service Coenraets s.a.  
Avenue Zénobe Gramme 7  
1480 Saintes - Belgium

VAT : BE 0464.600. 405

Phone : +32 (0) 2 367.89.00

Fax : +32 (0) 2 367.89.01

## TECHNICAL DATASHEET

info@tapeservice.be

www.tapeservice.be

# MULTI PURPOSE MASKING TAPE MSK 60

## Product description

Multi purpose masking tape for all masking jobs in the building and industrial sector, as well as for car body repair jobs. Temperature resistance up to 80°C (30min).

Recommended to remove within 48 hours.

Tape: Single sided

Adhesive: Natural rubber

Backing: Saturated paper

Color of the tape: white

## Application

- ✓ Car refinishing and repairing
- ✓ Decoration and building
- ✓ Multipurpose and maintenance

## Technical data

Adhesion	4.3N/25mm
Elongation to break	7.5%
Recommended time of temperature resistance	30mn
Temperature resistance	80°C
Tensile strength	85N/25mm
Total thickness	125µ
Weight of the backing	58g/m <sup>2</sup>

All technical data contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, nor can the information in itself be interpreted as a guarantee. Given the wide variety of applications of our products, the purchaser must question the suitability of the product(s) for each application and examine whether the intended products meet or can meet the set requirements. Before extensive use, the purchaser shall test the products. The purchaser shall bear exclusively all risks associated with the use of the products. Under no circumstances will Tape Service Coenraets be liable for any damage or costs incurred, nor for any indirect or accidental damage or costs incurred as a result of the use of the products.